

# **Technical Information**

## WashTechs 7420 IN C

#### Description

**WashTechs 7420 IN C** is a concentrated water dispersible saturated polyester polymer in solid form. The product is designed for as an anti back-staining agent in the garment wet processing of denim. It is also effective for use on cotton, polyester and blends.

#### **Benefits**

WashTechs 7420 IN C has the following beneficial characteristics.

- Highly concentrated
- Economical to use
- Disperses readily
- Prevents indigo dye redeposition
- Results in cleaner appearing garments
- Compatible with Cellulase Enzymes

### **Typical Properties**

Solids Content About 100% PH of Dispersion About 5

Color Off White to Beige

Texture Solid

Solubility Dispersible in water

Ionic Nature Nonionic

#### **Preparation**

**WashTechs 7420 IN C** must be dispersed in water prior to use. Dispersion concentrations of 15 - 25% solids are recommended. The product should be premelted and then added to hot water  $(45 - 50^{\circ}\text{C})$  at the desired concentration during agitation. The dispersion should be mixed thoroughly and cooled to  $30 - 35^{\circ}\text{C}$ . Biocide can be added if desired.

### **Application**

WashTechs 7420 IN C is recommended for use as an anti back-staining agent for garment washing. The product may be applied in the desize bath and / or the abrasion bath. Normal liquor ratios and temperatures for the desize and abrasion baths may be used.

## **Dosage**

**WashTechs 7420 IN C** (water dispersion at 25% solids) should be applied at 1.0 - 2.0% OWG. Dosage rate may be increased for lower solids dispersions.

## Handling

Please refer to the Material Safety Data Sheet for details.

## **Storage**

WashTechs 7420 IN C may be stored in a hot room if goods are scheduled for dispersion within one week. Storage in hot rooms can speed melting of the product prior to use. If the goods are not scheduled for use within one week, store in ambient temperature warehouse conditions.

# **Packaging**

**WashTechs 7420 IN C** is available in open head metal drums. Drums can be loaded on ISPM-15 compliant pallets upon request.

Date Established: 04/01/2014
Date Revised:

American Textile, LLC.
3235 Satellite Boulevard
Building 400, Suite 300
Duluth Georgia 30096
sales@americantextilellc.com
www.americantextilellc.com